

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
26 April 2001 (26.04.2001)

PCT

(10) International Publication Number
WO 01/29444 A1

(51) International Patent Classification⁷: F16F 1/06, 1/12,
15/067, F04B 17/04, 35/04

(21) International Application Number: PCT/NZ00/00202

(22) International Filing Date: 17 October 2000 (17.10.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
500681 21 October 1999 (21.10.1999) NZ
500683 21 October 1999 (21.10.1999) NZ

(71) Applicant (for all designated States except US): FISHER
& PAYKEL LIMITED [NZ/NZ]; 78 Springs Road, East
Tamaki, Auckland (NZ).

(72) Inventors; and


(75) Inventors/Applicants (for US only): ROKE, Lindsey,
Jack [NZ/NZ]; 22 Wanaka Place, Pakuranga, Auckland
(NZ). MCGILL, Ian, Campbell [NZ/NZ]; 88 Kohi-
marama Road, Kohimarama, Auckland (NZ). DUNCAN,
Gerald, David [NZ/NZ]; 12 Cedar Road, Epsom, Auck-
land (NZ). FERGUSON, William, George [NZ/NZ]; 3/8
Gilfillan Street, Blockhouse Bay, Auckland (NZ). TAY-
LOR, Andrew, Paul [NZ/NZ]; 139 Point View Drive,
Howick, Auckland (NZ).

(74) Agents: CALHOUN, Douglas, C. et al.; A J PARK,
Huddart Parker Building, 1 Post Office Square, Wellington
(NZ).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,

[Continued on next page]

(54) Title: LINEAR COMPRESSOR



(57) Abstract: A spring (50) for linear compressors has a pair of first mounting points (54) for securing to a first body. The spring (50) has at least one second mounting point (52) for securing to a second body which is reciprocable relative to the first body. A spring arm (52) spans between each of the first mounting points (54) by way of the second mounting point (52). In the preferred embodiment the sections of spring arm (52) extending between the first mounting points (54) and the second mounting point (52) include lengths which are of substantially constant radius of curvature. The spring (50) is to be constructed from a length of high fatigue strength wire bent into the required shape reducing the number of operations required in its manufacture.

WO 01/29444 A1